Back A4 Size Front



### **Ink Circulating Pump**

#### Flameproof Motorised / Pneumatic

- For Ink / Adhesive Circulation
- Minimized wastage of ink / adhesive
- 100 % Safe Flame-proof Motor
- S. S. Tank and Tray
- Flow Rate : 25 Ltrs/Min. (Water)
- Highly Efficient Flow Control Valve



Come to us with your Unanswered Questions.

Write to us in details at : info@arvindrubber.com

# **RECOR**



Core Saver /
Core Restorer

- Powered by Hydraulic Pump
- Load Capacity: 10,150 PSI (700 Bar)
- Proven Design
- Easy One-man Operation
- For restoration of core size 3"
- Optional adaptor is available for 6"

An ISO 9001:2008 Certified Company



Asia's No. 1 Manufacturer of Widest Range of Web Control Equipments



## World Class Web Control Equipments

An indisputable industry leader Since 1984

Asia's No. 1 Manufacturer of Widest Range of Web Control Equipments



# Trusted World Over Since 1984 sing Type

uick Look I Vertical Care Lifter I Care Besterer I Ink Circulating [

- 30 Years of Expertise
- Exporting since 27 years
- Exporting to 30+ countries
- 1400+ Clients (All Segments)
- Participation in
- 34 International Exhibitions
- Participation in

60+ Domestic Exhibitions



Inside A4 Size

### **Arvind**

### **APPLICATIONS**

- Gravure Printing
- ♦ Flexo Graphic Printing
- **♦** Solventless Lamination
- **♦** Solventbase Lamination
- Adhesive Coating

**POLYMERS AVAILABLE** 

Hypalone, NBR, HNBR, XNBR, Silicon, Neoprene, IIR (Butyl), EPDM etc.

**ROLLERS FOR SOLVENTLESS LAMINATION** 



## **Quick Change Sleeve**

Ideal for Solventless Lamination, Gravure Printing, Flexo Graphic Printing, Adhesive Coating



- Saves change over time
- **Highly Cost Effective** Light Weight - savings
- in transportation cost
- Vertical Storage
- Ease of operation
- Coatings available to suit all-and-every applications
- ♦ Almost readily available
- ♦ No metal erosion while re-coating. Thus, maintains shell strength and ensures better balancing of rollers.
- Proven Performance
- Anti-static property

### Wrinkle Removers

# **Expander Rollers**






- No Baggy Centres
- ♦ No Shrunk Width
- ♦ No Slack Edges











- Essential for thin web, 10 microns or less
- Performs excellent for separating the web after slitting, irrespective of web thickness
- Specially useful in Processing PP & HM
- Sizes : Dis.: 90mm to 140mm
- Length up to: 2500mm

### Rubber **Grooved Spreader**

- Popularly used on Film Plant
- Ideal for very delicate web like Metalized Film
- Individual groove type RH & LH
- Two or Four starts scroll type RH & LH



# **Core Holding Devices**



#### **Air Chucks**



# shafts



- Air Expandable Shafts
- Multi-Tube Air Shafts
- Ball Type Quick Lock Shafts
- Adaptor Shafts (from 3" to 6")

